

Bezel 8

3 in 1 Advanced Contact/ Contactless Unattended Device



The Bezel 8 is three in one device supporting Magnetic Stripe, Smart Card and Near Field Communication (NFC) functionalities. It has been developed to integrate seamlessly into vending machines and other unattended applications such as parking lots, transportation, petroleum stations. It conforms to IP and IK codes to meet outdoor deployments.

The Bezel 8 is equipped with a powerful 32-bit processor that is capable to process advanced contactless/contact applications.

Features and Benefits

The Bezel 8 with Linux OS allows remote downloading to update the firmware or applications. It is equipped with a high performance 32-bit processor that is capable handling advanced contactless/contact EMV applications. Bezel 8 comes with an encryption engine for handling data in highly secure payment environments. It supports EMV Contact L1 & L2, Contactless VISA PayWave, MasterCard PayPass, American Express, Discover D-PAS, ApplePay/VAS, Google Wallet, and Google Wallet /Smart Tap NFC applications.

- Delivers a compact all-in-one design for unattended vending applications
- Stylish outline
- Device manageable, service upgradeable
- All-in-one payment interface (ICC/MSR/Contactless)
- LCD display lets users know their contactless transactions processing status, plus multi color LED for better user interaction
- NFC Ready
- Linux Operating System
- Remote firmware download support
- Compliant with EVA mounting requirements
- Surface mount options
- USB and RS232 connectivities



Vending



Kiosk

Bezel 8

3 in 1 Advanced Contact/Contactless Unattended Device

Bezel 8 uses Linux Operating System and is capable of remote firmware download. It fully complies with European Vending Association (EVA) mounting requirements. It is a versatile device that interfaces with RS-232, USB, RJ-11 and Ethernet devices. It is powered either by USB or RS232 port.

Specifications

ELECTRICAL

Processor:	Main CPU: 32-bit processor / RF CPU: 32-bit processor
Magnetic Card Reader:	ISO7811; triple track reading
Smart Card Reader:	ISO7816; support 3V and 5V
SAM Module:	3 SAM module socket
Contactless:	All layers of ISO14443 Type A&B communication scheme / Support the ISO18092 NFCIP-1 standard

MECHANICAL

Weight:	< 350g
Dimensions:	L :105 mm x W: 84 mm x D:48 mm
Material:	PC+ABS, 94V-0
Display:	LCD display (128x64 Mono Graphic LCD with backlit)
Light:	Flash light pipe for MSR and ICC for guiding indication and audience attraction
Mounting:	Compliant with EVA mounting requirements /Surface mount option

SECURITY REQUIREMENT

DES, 3DES, SHA, MAC, AES and RSA encryption algorithms

INTERFACES

RJ11 :	EPP/ Peripheral
RJ50 :	USB/ RS232
RJ45 :	Ethernet

ENVIRONMENTAL

Operating Temperature:	:-20 °C to 70 °C
Storage Temperature:	-30 °C to 80 °C
Operating Humidity:	5% to 95% (Non condensing)
Storage Humidity:	5% to 95% (Non condensing)
Enclosure:	UV exposure resistance
IP Rating:	54
IK Rating:	06

POWER REQUIREMENTS

Input Voltage:	USB power or 5V/1A from RS232
Battery RTC life:	5 years

CERTIFICATION REQUIREMENT

EMV:	EMV Contact L1 & L2; EMV Contactless L1
Payment Card:	Visa payWave / MasterCard Paypass /American Express / Discover D-PAS
Regulations:	FCC Class B; FCC ID; CE Class B; RoHS



UIC USA

47341 Bayside Parkway, Fremont,
CA94538, USA
Tel: 510-438-6799 Fax: 510-438-6790
info@uicusa.com

UIC Taiwan

1F, No.1, Ln 15, Ziqiang St., Tucheng Dist.,
New Taipei City 236, Taiwan.
Tel: 886-2-2268-7075 Fax: 886-2-2269-5686
salessupport@uniform.com.tw

UIC Europe GmbH

Daimlerstraße 6, 61449 Steinbach
am Taunus, Germany
Tel: +49 6171 2088 Fax: +49 6171 2088 413
info@uiceurope.com