



> Unattended

# Bezel 8

## 3 in 1 Advanced Contact/ Contactless Unattended Device



The Bezel 8 is three in one device supporting Magnetic Stripe, Smart Card and Near Field Communication (NFC) functionalities. It has been developed to integrate seamlessly into vending machines and other unattended applications such as parking lots, transportation, petroleum stations. It conforms to IP and IK codes to meet outdoor deployments.

The Bezel 8 is equipped with a powerful 32-bit processor that is capable to process advanced contactless/contact applications.

## Features and Benefits

The Bezel 8 with Linux OS allows remote downloading to update the firmware or applications. It is equipped with a high performance 32-bit processor that is capable handling advanced contactless/contact EMV applications. Bezel 8 comes with an encryption engine for handling data in highly secure payment environments. It supports EMV Contact L1 & L2, Contactless VISA PayWave, MasterCard PayPass, American Express, Discover D-PAS, Google Wallet, and Google Wallet/Smart Tap NFC applications.

- Delivers a compact all-in-one design for unattended vending applications
- Stylish outline
- Device manageable, service upgradeable
- All-in-one payment interface (ICC/MSR/Contactless)
- LCD display lets users know their contactless transactions processing status, plus multi color LED for better user interaction
- NFC Ready
- Linux Operating System
- Remote firmware download support
- Compliant with EVA mounting requirements
- Surface mount options
- USB and RS232 connectivities



Vending



Kiosk



# Bezel 8

## 3 in 1 Advanced Contact/Contactless Unattended Device

Bezel 8 uses Linux Operating System and is capable of remote firmware download. It fully complies with European Vending Association (EVA) mounting requirements. It is a versatile device that interfaces with RS-232, USB, RJ-11 and Ethernet devices. It is powered either by USB or RS232 port.

## Specifications

### ELECTRICAL

Processor:	Main CPU: 32-bit processor / RF CPU: 32-bit processor
Magnetic Card Reader:	ISO7811; triple track reading
Smart Card Reader:	ISO7816; support 3V and 5V
SAM Module:	3 SAM module socket
Contactless:	All layers of ISO14443 Type A&B communication scheme / Support the ISO18092 NFCIP-1 standard

### MECHANICAL

Weight:	< 350g
Dimensions:	L :105 mm x W: 84 mm x D:48 mm
Material:	PC+ABS, 94V-0
Display:	LCD display (128x64 Mono Graphic LCD with backlight)
Light:	Flash light pipe for MSR and ICC for guiding indication and audience attraction
Mounting:	Compliant with EVA mounting requirements /Surface mount option

### SECURITY REQUIREMENT

DES, 3DES, SHA, MAC, AES and RSA encryption algorithms

### INTERFACES

RJ11 :	EPP/ Peripheral
RJ50 :	USB/ RS232
RJ45 :	Ethernet

### ENVIRONMENTAL

Operating Temperature:	:-20 °C to 70 °C
Storage Temperature:	-30 °C to 80 °C
Operating Humidity:	5% to 95% (Non condensing)
Storage Humidity:	5% to 95% (Non condensing)
Enclosure:	UV exposure resistance
IP Rating:	54
IK Rating:	06

### POWER REQUIREMENTS

Input Voltage:	5V/1A
Battery RTC life:	5 years

### CERTIFICATION REQUIREMENT

EMV:	EMV Contact L1& L2; EMV Contactless L1
Payment Card:	Visa payWave / MasterCard Paypass /American Express / Discover D-PAS
Regulations:	FCC Class B; FCC ID; CE Class B; RoHS



### UIC USA

47341 Bayside Parkway, Fremont, CA 94538, USA  
Tel: 510-438-6799 Fax: 510-438-6790  
info@uicusa.com

### UIC Taiwan

1F, No.1, Ln 15, Ziqiang St., Tucheng Dist., New Taipei City 236, Taiwan.  
Tel: 886-2-2268-7075 Fax: 886-2-2269-5686  
salessupport@uniform.com.tw